## **Mississauga Forklift Training Course**

Mississauga Forklift Training Course - OSHA and CSA establish criteria for forklift safety training that meets current regulations and standards. Anybody intending to operate a forklift is required to successfully complete safety training prior to utilizing whatever kind of forklift. The accredited Forklift Operator Training Program is meant to provide trainees with the knowledge and practical skills to become an operator of a forklift.

Vehicle and Mobile Equipment safety rules which apply to forklift operation consist of pre-shift inspections, and rules for lifting and loading.

Prior to a shift beginning, an inspection checklist should be done and given to the Supervisor or Instructor. If whichever maintenance issue is discovered, the machine should not be utilized until the problem is dealt with. To indicate the machine is out of order, the keys should be removed from the ignition and a warning tag placed in a spot that is visible.

Loading safety regulations comprise checking the forklift nameplate's rating capacity and knowing if the load weight falls within capacity. The forklift forks should be in the down position when the forklift is starting up. Don't forget that there is a loss of approximately one hundred pounds carrying capacity for every inch further away from the carriage that the load is carried.

Lifting must start with the driver moving to a stopped position around three inches from the load. The mast should then be leveled until it has reached a right angle with the load. Raise the forks to one inch below the slot on the pallet and drive forward. After that lift forks four inches. Tilt back the load to secure it for moving. Drive the lift backwards if the load obscures frontal vision. Check behind and honk to warn other employees. Do not allow forks to drag on the ground.

Forklift loads must be loaded in such a way that they are secure and do not create a hazard to other people or objects. Restraining loads is necessary for materials that might shift during transport and destabilize the forklift.

So as to avoid the movement of drums, drums could be strapped together to reduce movement. Operators of forklifts must drive slowly when transporting liquids, to reduce instability in the forklift.