

## Mississauga Overhead Crane Operator Training

Mississauga Overhead Crane Operator Training - The program teaching overhead crane operator training has been meant specifically to instruct trainees on the fundamentals of pre-shift inspections and overhead crane/sling operation. The programs are instructed by expert trainers and consultants. Well-trained staff are more efficient and productive, that actually saves on costs associated with merchandise damage, property damage, and accidents due to the use of incorrect operating procedures. Our overhead crane certification is customized for staff who have literacy barriers, reducing certification time by 50 percent.

Overhead cranes are best for particular repetitive hoisting activities. This type of crane has wide ranging capacities. They could be used for specialized lifting jobs like removing or installing major plant machinery.

Worker and operators should employ safe rigging practices in order to safely operate an overhead crane. This would require both practice and knowledge as the load needs to be properly rigged to ensure its stability when raised. Prior to beginning a hoisting job, it must be determined that the crane is suitable for the task, with correct travel, lift and capacity. The crane must be subjected to a thorough visual and physical inspection before use. The capacity of all equipment, including the rope, slings and hardware, must never exceed load weight capacities.

Prior to using the rigger needs to know what sling is right for each lift and must check the rigging hardware and gear. The communications which are used with the crane operator must be clear and concise. A signaler must be chosen for the role and signals have to be agreed upon. The crane operator has to follow directions just from the chosen individual. If a remote or wired controller is being used, the operator should be trained in all its functions.

To be able to ensure the safety of workers, a warning needs to be issued and the path of the load must be cleared of all obstacles before the lift starts. Individuals must not be allowed to walk under the lift loads. The crane hoist must be centered over the load before lifting in order to prevent swinging. The safety catch must be closed immediately after sliding the sling fully onto the hoisting hook. Unused sling legs should be secured so they do not drag. Never leave loose materials on a load being lifted. Watch that fingers and hands are clear when slack is taken out of a sling. Before the lift is carried out, step clear of the danger zone.